

# ENELTEC®

brighten your ideas

## T5 LED Tubes





### Specifications:

- Voltage: 100-240 / 85-265VAC
- Color: 2800-3300K / 4000-4500K / 5500-6000K
- Operating temperature: -35 to + 50°C
- Material: PC cover & Aluminum back
- Light Degradation: < 5% in 30,000 hours
- Warranty: 3 years



Eneltec Group / Global Marketing Center / Eneltec (Shanghai) Co., Ltd.  
Tel: 86-21-33811921      86-21-33811922      Fax: 86-21-33811923  
E-mail: [sales@eneltec-led.com](mailto:sales@eneltec-led.com)      <http://www.eneltec-led.com>

Model	Dimension (mm)
ENLT-T5060	604 Φ15
ENLT-T5120	1204 Φ15
ENLT-T5150	1504 Φ15



## Applications:

High power LED Tube are designed for use in supermarkets, jeweller's shops, advertisement box, office building, or for direct replacement of conventional lamps.

## Features and advantages:

- Direct replacement of conventional lamps
- LED life of 50,000 hours continuous work
- No hazard of mercury or lead entering the environment
- Solid-state, shock and vibration resistant light sources runs on
- Major reduction in power costs, maintenance free
- Generate little heat
- No fluorescent flickering
- No danger of broken glass
- Internal power supply with high power factor & low harmonic current



## Testing Data:

Model	ENLT-T5060-NI-01	ENLT-T5120-NI-01	ENLT-T5150-NI-01	ENLT-T5060-I-01	ENLT-T5120-I-01	ENLT-T5150-I-01
Voltage	100-240VAC			85-265VAC		
LED	72pcs SMD2835	168pcs SMD2835	216pcs SMD2835	72pcs SMD2835	168pcs SMD2835	216pcs SMD2835
Power	9	18	22	9	18	22
PF	0.95					
Lumen	800	1700	2050	800	1700	2050
Beam Angle	120°					
Color	2800-3300K / 4000-4500K / 5500-6000K					
Cover	Clear/Frosted					
Driver	Non Isolated Driver			Isolated Driver		

## Packing:

Model	ENLT-T5060-NI-01	ENLT-T5120-NI-01	ENLT-T5150-NI-01	ENLT-T5060-I-01	ENLT-T5120-I-01	ENLT-T5150-I-01
Packing Dimension (mm)	627x240x250	1270x240x250	1570x240x250	627x240x250	1270x240x250	1570x240x250
Quantity	30PCS					
Net Weight (kg)	4.8	9.3	13.5	4.8	9.3	13.5
Gross Weight (kg)	7.0	12.5	15.0	7.0	12.5	15.0

## Warning:

1. It is non-waterproof.
2. Please do not touch it when they are light.
3. Please use traditional coop transformer and switch for power supply. Do not use traditional electronic transformer for power supply.
4. The angle of emitting light can be designed according to the client's requirements